

TEST REPORT

CLIENT	Go Green

TEST METHOD CONDUCTED	ASTM D1335 Standard Test Method for Tuft Bind of Pile Yarn Floor
IEST METHOD CONDUCTED	Coverings

DESCRIPTION OF TEST SAMPLE		
IDENTIFICATION	Aquamaxx 90	
ROLL NUMBER	G36711B	
CONSTRUCTION	Turf	
REFERENCE	PO #17807	

GENERAL PRINCIPLE

This test method is designed to measure the force required to pull a tuft completely out of a pile floor covering. It is applicable to both cut and looped pile construction. In the event the material contains both cut and loop, only the loop pile is tested.

TEST RESULTS

10.8	11.0	9.8	12.0	10.6
9.9	11.5	10.4	12.1	10.8
11.3	12.2	10.2	13.2	11.4

AVERAGE TUFT BIND	11.1 Lbs.

APPROVED BY

NVLAP

This facility is accredited by the National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code 100297. This accreditation does not constitute an endorsement, certification, or approval by NIST or any agency of the United States Government for the product tested. This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical or similar products. This report, or the name of Professional Testing Laboratory, LLC, shall not be used under any circumstance in advertising to the general public.

PJLA Testing Accreditation #93341

714 Glenwood Place Dalton, GA 30721 706-226-3283 Fax: 706-226-6787 protest@optilink.us