


GOGREEN

ENGINEERED TURF PRODUCTS



SCAN FOR
WEBSITE



AQUAMAXX® 50

KEY FEATURES

- 100% drainage backing system - drains at >600 in/hr
- Water and waste drain directly through the backing – Fast drainage and our exclusive backing reduces pet odors and kills bacteria
- Thermally stable, wrinkle free backing
- Fiber Cooling Technology - lowers lawn surface temperature
- Created with an incredible tuft bind; dogs won't be able to dig through the extremely tough backing
- Enhanced fiber memory creates increased resilience while giving a soft feel and realistic look



AQUA MAXX

RECOMMENDED APPLICATIONS



FOOT TRAFFIC



PRODUCT SPECIFICATIONS

| | |
|---------------|---|
| YARN TYPE: | POLYETHYLENE MONOFILAMENT & POLYPROPYLENE |
| YARN COLOR: | SPORT GREEN, APPLE GREEN, & OLIVE GREEN |
| THATCH COLOR: | FIELD GREEN & TAN |
| FACE WEIGHT: | 50 OZ/SY |
| PILE HEIGHT: | 1" |
| BACKING: | 16 OZ BLACK URETHANE |
| WARRANTY: | 15 YEAR PRO RATED WARRANTY |



844.368.4765 | WWW.GOGREENSYNTURF.COM



GO GREEN

ENGINEERED TURF PRODUCTS

AQUAMAXX® 50

| | |
|--|------------|
| AATCC 134 - ANTI-STATIC | N/A |
| ASTM C1028 - STATIC/FRICTION | N/A |
| ASTM D1335 - TUFT BIND | 12 LB |
| ASTM F2765 - LEAD LEVELS | <0.01 PPM |
| ASTM D2859 - FLAMMABILITY (PILL TEST) | PASS |
| ASTM E648 - FLAMMABILITY (CRITICAL RADIANT FLUX) | CLASS I |
| ASTM 5034 - GRAB TEAR STRENGTH | N/A |
| ASTM F1951 - ADA WHEELCHAIR | N/A |
| ASTM F1551 - WATER PERMEABILITY | >600 IN/HR |
| ASTM E108 - FIRE TEST (ROOF DECKS) | N/A |
| ASTM E84 - SURFACE FLAMMABILITY/SMOKE DENSITY | N/A |
| ASTM 1292 - IMPACT ATTENUATION | PASS |



AQUA MAXX