

## ENGINEERED TURF PRODUCTS



SCAN FOR WEBSITE



## HEATMAXX SOFT™ 65

- 100% New Proprietary Nylon yarn construction delivers superior preformance that is "Soft as Poly, Strong as Nylon".
- NO INFILL REQUIRED! Fiber and turf design keeps fibers upright even in heavy use areas.
- Class A Fire Rating- the only turf warranted against reflective burns from Low E Windows.
- Certified for all indoor applications and exterior rooftops.
- 100% ADA wheelchair compliant and meets safety standards!



**HEATMAXX SOFT ™** 

RECOMMENDED APPLICATIONS

FOOT TRAFFIC











## PRODUCT SPECIFICATIONS

YARN TYPE: NYLON

YARN COLOR: VERDE & LIME GREEN

THATCH COLOR: VERDE GREEN TAN

FACE WEIGHT: 65 OZ/SY

PILE HEIGHT: 1-5/8"

BACKING: BLACK URETHANE

WARRANTY: 15 YEAR PRO RATED WARRANTY











## ENGINEERED TURF PRODUCTS

HEATMAXX SOFT™ 65	
AATCC 134 - ANTI-STATIC	PASS
ASTM C1028 - STATIC/FRICTION	PASS
ASTM D1335 - TUFT BIND	16.5 LB
ASTM F2765 - LEAD LEVELS	<0.01 PPM
ASTM D2859 - FLAMMABILITY (PILL TEST)	PASS
ASTM E648 - FLAMMABILITY (CRITICAL RADIANT FLUX)	PASS
ASTM 5034 - GRAB TEAR STRENGTH	PASS
ASTM F1951 - ADA WHEELCHAIR	COMPLIANT
ASTM F1551 - WATER PERMEABILITY	>600 IN/HR
ASTM E108 - FIRE TEST (ROOF DECKS)	CLASS A
ASTM E84 - SURFACE FLAMMABILITY/SMOKE DENSITY	CLASS C

